

Compact, Sturdy
Easy to Maneuver

S65



Sullair **65** (3,7 m³/min - 131 CFM)

- SULLAIR air end **with 2-year warranty**
- **KUBOTA** water cooled **engine**
robust and reliable
- **Optimum accessibility** for Ease of Maintenance
- **Composite canopies** to withstand the rigours
of site abuse
- **Progressive control** for “on demand” Efficiency

Screw compressor



SULLAIR manufactured air end, built in compliance with the requirements of the standard **ISO 9001**.

Low running costs. The air end comes with a 2-year warranty.

Composite canopy



Made of ABS-ASA and polyethylene, these canopies boast numerous assets (high UV and weather stability). Canopy made of 5 different **easily replaceable** panels.

KUBOTA engine



Diesel water-cooled engines, well known for their **reliability**.

Their cooling system means they can be used in **high ambient temperatures**.

Full control panel



Transparent lockable door, including a pressure gauge, hour clock, preheating contact and signal lamp, safety and charge indicator lamps. **Accessible fuse box**.



S65

Air flow control

The progressive regulation control optimises the flow according to the air consumption.

Safety devices:

- Safety systems:
- engine water temperature
 - engine oil pressure
 - compressor air outlet temperature
 - safety device protects starter.

Statutory road signalling.

Air filters with safety cartridges

Positioned so as to recover the fresh air from outside:

- engine filter
- compressor filter

Tool box

To store a paving breaker, hose and steels.

Design

Easy to maneuver/handle road trailer. Easy access to all components.

Options :

- Corporate Canopy Colours available.
- 12/24 V transformer.
- Anti-theft chain.
- Fluid Catch tank.
- Line lubricator.
- Hose Reel.

These products are made according to the most stringent standards within the scope of an ISO 9001 certified system.

Your **SULLAIR** authorised distributor

SPECIFICATIONS

65

CE Compressor* model	65
Delivery (1) m ³ /min (cfm)	3,7 - (131)
Rated pressure, bar (psi)	7 - (100)
Compressor oil, liters	7,8
Body	
Fuel tank capacity, liters	55
Air outlets	2 x 3/4"
Optional air outlet	1"
Total weight wet (2) kg	698 - 727 - 703
Maximum axle weight (2) kg	750 - 860 - 860
Total length (2) m	2,93 - 3,10 - 3,13
Total width (2) m	1,45 - 1,45 - 1,45
Height (2) m	1,39 - 1,39 - 1,39
Kubota engine	V 2203 M
Number of cylinders	4
Displacement cm ³	2187
Rated speed, rpm	2250
Rated power kW (HP)	30 - (40,8)

(1) at rated pressure according to ISO 1217 (±5%)

(2) NF = unbraked,
F = braked with adjustable towbar
UK = braked with straight towbar